

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR

METHOD AND APPARATUS FOR EMULATING A LOCAL DATA PORT

Inventor(s): Kevin W. Bross
Monte G. Johnson

Prepared by:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN, LLP
12400 Wilshire Boulevard, 7th Floor
Los Angeles, California 90025
(503) 684-6200

"Express Mail" label number EL034433907US

METHOD AND APPARATUS FOR EMULATING A LOCAL DATA PORT

FIELD OF THE INVENTION

The present invention relates to the field of computer system networking.

- 5 More specifically, the present invention relates to how data is communicated among network devices.

BACKGROUND OF THE INVENTION

- As technology moves toward faster utilization of devices, multifunction
10 devices (MFDs), such as printer/fax/scanner devices, printers, and scanners, communication between the devices and computers becomes important. Additionally, the devices are being networked to provide utilization of the a limited number of devices by several computers at any given time. However, devices that are locally connected communicate differently compared to devices that are
15 networked.

- Networking several computers with devices reduces the capabilities of two way communication of data between the computers and the devices because of the way data is communicated through networking. Local communication of data between computers and devices provides a more direct two-way communication
20 of data between computers and the devices.

A typical method for networking devices, such as printers, involves using a device server port monitor software to redirect device requests across the network. In other cases, a network driver allows printer ports to be redirected. In

most situations, the printer driver sends the printing data to the port monitor or network redirection layer. The port monitor and layers below are responsible for ensuring the job is properly printed (the printer driver has totally completed its job and given the data to the port monitor).

5 Some device drivers bypass the port monitor interface and write directly to a communication layer. This allows for more direct manipulation of the device, but it usually means that the device can no longer be networked. As more people try to network these devices, the approach of bypassing the port monitor interface and writing directly to the communication layer becomes increasingly
10 difficult. This approach is made even worse when device drivers bypass the communication layer entirely and send device data directly to the parallel port hardware, such as the Super I/O chip in the computer. If communication like this is required, the printer cannot be networked.

 Additionally, if a device is networked, communication between more than
15 one computer and the networked device is difficult due to the device being busy receiving a request from one of the computers. The other computers on the network must wait until the receiving of data by the networked device is complete.

 Because of communicating locally is different from communicating across
20 a network, devices for the network cannot be locally connected and local devices cannot be networked without difficulty.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not by way of limitation in the figures of the accompanying drawings, in which the like references indicate similar elements and in which:

5 **Figure 1** illustrates an example of network communications with a printer device;

Figure 2 illustrates an example of communication and manipulation of a local device;

10 **Figure 3** illustrates one embodiment of the present invention for facilitating emulation of local data communications between networked devices;

Figure 4 illustrates one embodiment of the present invention for facilitating local data communications between two networked devices;

Figure 5 is a flow chart illustrating a method for emulating a local data port according to one embodiment of the present invention; and

15 **Figure 6** illustrates a computer system upon which an embodiment of the present invention can be implemented.

00750 3340750

DETAILED DESCRIPTION

In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, those skilled in the art will understand that the present invention may be

5 practiced without these specific details, that the present invention is not limited to the depicted embodiments, and that the present invention may be practiced in a variety of alternate embodiments. In other instances, well known methods, procedures, components, and circuits have not been described in detail.

10 Parts of the description will be presented using terminology commonly employed by those skilled in the art to convey the substance of their work to others skilled in the art.

Various operations will be described as multiple discrete steps performed in turn in a manner that is helpful in understanding the present invention.

15 However, the order of description should not be construed as to imply that these operations are necessarily performed in the order they are presented, or even order dependent. Lastly, repeated usage of the phrase "in one embodiment" does not necessarily refer to the same embodiment, although it may.

Figures 1 and 2 illustrate a prior art embodiment for network data communications and a prior art embodiment of local data communications.

20 **Figure 1** illustrates an example of network communications with a printer device, however, it should be appreciated that any other type of networked device known in the art such as, but not limited to, a multifunctional device (MFD) can be used. Illustrated in **Fig. 1**, is an example of a computer with an operating

system application such as, but not limited to, the Windows® operating systems, available from Microsoft Corporation of Redmond, Washington. Alternate embodiments may be implemented in other programming approaches known in the art.

5 In **Fig. 1**, a computer **150** is running an application **105**. Incorporated in the application **105** is a device driver **110** which facilitates the sending of data to a networked device **100**. The device driver **110** incorporates a port monitor/network layer **115**. The port monitor/network layer **115** facilitates redirection of local device data across the network through the network port **125** to the networked device **100**. In the illustrated prior art of **Fig. 1**, the device driver **110** sends a signal **112** to the port monitor/network layer **115** (i.e., a command signal to generate network packet data signals). The port monitor/network layer **115** is responsible for ensuring that the device data is properly executed by converting the local device data into network port packet data signals **120** for transmission onto the network (i.e., the device driver **110** completes sending the printing data to the port monitor/network **115**). The network port packet data signals **120** are sent through the network port **125** to the networked device **100**, which is connected to a network (not shown).

Due to communicating through a network using network port packet data signals, communications between the computer **150** and the networked device **100** is unreliable and not direct. Even though networking the device allows for more than one user to utilize the networked device, networking the device does not allow for direct communication between the computer and the device.

device, thereby, improving two-way communication of data between devices,
while utilization of a device by several users.

Figure 3 illustrates one embodiment of the present invention for facilitating emulation of local data communications between networked devices. In **Fig. 3**, a
5 computer **320** is running the application **105**, and incorporated in the application is the device driver **110**. The device driver **110** incorporates a device communication layer **210** for converting local device data into local port pin data signals **215**.

Shown in **Fig. 3**, the device driver **110** sends a signal **209** to the device
10 communication layer **210** (i.e., a command signal to generate local port pin data signals). The local port pin data signals **215** are received by a computer virtual port **310** in accordance with the teachings of the present invention. The computer virtual port **310** is a network port that emulates a local port (i.e., a parallel port such as, but not limited to, a line print terminal). That is, the virtual
15 port **310** converts the local port pin data signals **215** to network port packet data signals **340** for transmission onto the network **350**.

Illustrated in **Fig. 3**, the network port packet data signals **340** are routed through the network **350** and received by the networked device **300**. Any number of network routing techniques known in the art may be used.

20 Incorporated with the networked device **300** is a device virtual port **330** in accordance with the teachings of the present invention. The device virtual port **330** receives the network port packet data signals **340** from the network **350**. Much like the virtual port **310**, the device virtual port **330** is a network port that

emulates a local port based upon the signal received from the network **350**. That is, the device virtual port **330** converts the network port packet data signals **340** to local port pin data signals **360** for sending to the networked device **300**.

Additionally, in **Fig. 3**, information from the networked device **300** such as, but not limited to, status of ink level, paper level, toner level, etc., will be sent as local port pin data signals **215** to the device virtual port **330**. Again, the virtual port **330** emulates a local port such as, but not limited to, a LPT1. The device virtual port **330** converts the local port pin data signals **360** to network port packet data signals **340** for transmission on to the network **350**.

The computer virtual port **310** receives the network port packet data signals **340** from the network **350**. Much like the virtual port **330**, the computer virtual port **410** emulates a local port based upon the signal received from the network **350**. That is, the computer virtual port **310** converts the network port packet data signals **340** to local port pin data signals **215** for sending to the computer **320**, where the computer **320** will receive the information from the networked device **300** such as, but not limited to, status of ink level, paper level, toner level, print head temperature, etc.

As shown in **Fig. 3**, a networked device can communicate with a computer as if the device and the computer were locally connected, thereby, allowing a devices to be networked, while maintaining locally connected data communication capabilities between the networked devices.

Figure 3 illustrates one embodiment showing the present invention, virtual ports **330** and **310**, as components outside of the devices **300** and **320**. In an

alternate embodiment, the functionality of the present invention, virtual ports **310** and **330**, may be executed as software within the devices **300** and **320**.

Figure 4 illustrates one embodiment of the present invention for facilitating local data communications between two networked devices. In **Fig. 4**, both
5 computer #1 **401** and computer #2 **402** are each running an operating system application **405** and **435**. Incorporated in each operating system application **405** and **435** is a device driver **410** and **440**. Each device driver **410** and **440** incorporates a device communication layer **415** and **445** for converting local device data into local port pin data signals **480** and **481**. Additionally,
10 incorporated in each computer **401** and **402**, is a virtual port **430** and **460** and an intermediate device driver **420** and **450**. Each intermediate driver **420** and **450** includes a cache memory **425** and **426**.

In **Fig. 4**, before the start of a device request, virtual port #1 **430** retrieves device status such as, but not limited to, toner level, paper level, etc., from the
15 networked device **465** before computer #1 **401** sends a device request. Since the retrieved data is achieved through the virtual port #1 **430** and device virtual port, as discussed above with reference to **Fig. 3**, the communication between the intermediate driver #1 **420** and the networked device **465** will be as if communicating locally, even though the communication is through a network
20 **475**. The retrieved data is stored in the cache memory **425** of the intermediate driver #1 **420**. Once the retrieved data is stored, computer #1 **401** sends a device request such as, but not limited to, a print request to the networked device **465**. Since a local port connection is being emulated, networked device **465** will

be unavailable to other networked devices, while servicing the device request from computer #1 **401**.

Illustrated in **Fig. 4**, before the device request of computer #1 **401** is complete, computer #2 **402** sends a device request to the networked device **465** through the virtual port #2 **460** emulating a second local port connection. When the device request of computer #2 **402** reaches the device virtual port **470**, the device virtual port refuses the connection because only one local port connection can be serviced at a time. Virtual port **470** sends a busy signal with the internet protocol (IP) address of the occupying computer (computer #1 **401**) back to the virtual port #2 **460**.

Once the busy signal and the IP address are received by virtual port #2 **460**, virtual port #2 **460** can send a request along with the IP address to the intermediate driver #2 **450** to retrieve the information stored in the cache memory **425** of intermediate driver #1 **420** through the network **475**. In response to the request, the intermediate driver #2 **450** retrieves the information from the intermediate driver #1 **420**. In other words, information about a first networked device, such as, but not limited to, paper level, toner level, ink level, print head temperature, busy status, etc., may be communicated to one or more additional networked devices even though the first networked device may be busy with an emulated local request.

Figure 5 is a flow chart illustrating a method for emulating a local data port according to one embodiment of the present invention. A signal is received from a local device such as, but not limited to, a computer **510**. The signal is

converted to a network port packet data signal to emulate a local data signal port
520. The network port packet data signal is transmitted to a remote device over
a network connection 530.

Figure 6 illustrates a computer system 600 upon which an embodiment of
5 the present invention can be implemented. The computer system 600 includes a
processor 601 that processes data signals. The processor 601 may be a
complex instruction set computer (CISC) microprocessor, a reduced instruction
set computing (RISC) microprocessor, a very long instruction word (VLIW)
microprocessor, a processor implementing a combination of instruction sets, or
10 other processor device. **Figure 6** shows an example of the present invention
implemented on a single processor computer system 600. However, it is
understood that the present invention may be implemented in a computer system
having multiple processors. The processor 601 is coupled to a CPU bus 610 that
transmits data signals between processor 601 and other components in the
15 computer system 600.

The computer system 600 includes a memory 613. The memory 613 may
be a dynamic random access memory (DRAM) device, a synchronous direct
random access memory (SDRAM) device, or other memory device. The memory
613 may store instructions and code represented by data signals that may be
20 executed by the processor 601.

A bridge/memory controller 611 is coupled to the CPU bus 610 and the
memory 613. The bridge/memory controller 611 directs data signals between the
processor 601, the memory 613, and other components in the computer system

600 and bridges the data signals between the CPU bus 610, the memory 613, and a first I/O bus 620.

The first I/O bus 620 may be a single bus or a combination of multiple buses. As an example, the first I/O bus 620 may comprise a Peripheral

5 Component Interconnect (PCI) bus, a Personal Computer Memory Card International Association (PCMCIA) bus, a NuBus, or other buses. The first I/O bus 620 provides communication links between components in the computer system 600. A network controller 621 is coupled to the first I/O bus 620. The network controller 621 links the computer system 600 to a network of computers

10 (not shown in **Figure 6**) and supports communication among the machines. A display device controller 622 is coupled to the first I/O bus 620. The display device controller 622 allows coupling of a display device (not shown) to the computer system 600 and acts as an interface between the display device and the computer system 600. The display device controller 622 may be a
15 monochrome display adapter (MDA) card, a color graphics adapter (CGA) card, an enhanced graphics adapter (EGA) card, an extended graphics array (XGA) card or other display device controller. The display device (not shown) may be a television set, a computer monitor, a flat panel display or other display device.

The display device receives data signals from the processor 601 through the
20 display device controller 622 and displays the information and data signals to the user of the computer system 600.

A second I/O bus 630 may be a single bus or a combination of multiple buses. As an example, the second I/O bus 630 may comprise a PCI bus, a

PCMCIA bus, a NuBus, an Industry Standard Architecture (ISA) bus, or other buses. The second I/O bus **630** provides communication links between components in the computer system **600**. A data storage device **631** is coupled to the second I/O bus **630**. The data storage device **631** may be a hard disk drive, a floppy disk drive, a CD-ROM device, a flash memory device or other mass storage device. A keyboard interface **632** is coupled to the second I/O bus **630**. The keyboard interface **632** may be a keyboard controller or other keyboard interface. The keyboard interface **632** may be a dedicated device or can reside in another device such as a bus controller or other controller. The keyboard interface **632** allows coupling of a keyboard (not shown) to the computer system **600** and transmits data signals from a keyboard to the computer system **600**. An audio controller **633** is coupled to the second I/O bus **630**. The audio controller **633** operates to coordinate the recording and playing of sounds.

A bus bridge **624** couples the first I/O bus **620** to the second I/O bus **630**. The bus bridge **624** operates to buffer and bridge data signals between the first I/O bus **620** and the second I/O bus **630**.

In one embodiment, the virtual port, as described above, is implemented using one or more computers such as the computer system of **Fig. 6**. In one embodiment, the present invention is implemented as software routines executed by one or more execution units within the computer(s). For a given computer system, the software routines can be stored on a storage device, such as memory **613**.

In one embodiment, the software routines are written in the C programming language. It should be appreciated that the software routine may be implemented in any of a wide variety of programming languages. In alternate embodiments, the present invention is implemented in discrete hardware or
5 firmware. For example, one or more application specific integrated circuit (ASICs) could be programmed with one or more of the above described functions of the device server. In another example, one or more functions of the device server could be implemented in one or more ASICs on additional circuit boards, and the circuit boards could be inserted into the computer(s) described above. In
10 another example, field programmable gate arrays (FPGAs) or static programmable gate arrays (SPGAs) could be used to implement one or more functions of the present invention. In yet another example, a combination of hardware and software could be used to implement one or more functions of the present invention.

15 Thus, a method and apparatus for emulating network and local ports and network and local port signals is described.

In the forgoing description, the invention is described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the
20 broader spirit and scope of the present invention as set forth in the appended claims. The specifications and drawings are accordingly to be regarded in an illustrative rather than in a restrictive sense.